

Terminal Tractor/Yard Spotter

Used Yard Spotter Everett - Tow tractors, also called tow tugs or towing tractors are popular for moving loads horizontally in airports, arenas, warehouses, manufacturing plants and other large buildings. They are capable of towing several trailers in a train formation. Tow tractors can move aircraft into and outside of airport locations such as terminals and hangars. Tractive effort is how these machines transport loads. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. Tractive effort says that the heavier the load, the more tractive effort is required. Based on this principle, the tow tractor works by lifting a part of the load it is towing while making sure the load's wheels remain on the ground. The tractive effort is increased by the unit's hydraulic mast. This has been engineered to produce downforce on the drive wheel directly under the mast. The traction created by this process enables the tow tractor to pull very large and heavy loads. Types of Tow Tractors Heavy-duty tow tractors and load carriers are two types of tow tractors. Load Carriers Numerous businesses need to transport items of different sizes on a regular basis including manufacturing, parcel delivery services and airport baggage. Tow tugs or load carrier tow tractors are excellent for these jobs as they can maneuver single items stacked on wheeled platforms for streamlined transport. The category that load carrier tow tractor models fall into includes forklift trucks, cranes and pallet jacks. Load carrier tow tugs transport loads at ground level only, rather than lifting or lowering off the ground or from shelving or other hard to reach areas. In order to be ready for transport, items must be secured on a wheeled platform or already on wheels to use the tow tractor. Bogies, skates and trollies are other names for wheeled platforms. The tow tractor joins to the trolley and functions similarly to a train locomotive. Usually, the tow tug has a male-end steel coupling that couples to the female-end fixed to the front of the trolley. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. Tow tractors with a train of trollies enable a wider range in the type of items that can be transported and in the types of conditions they can be transported. Trolley types differ to provide customization options. Trollies can connect together and are compatible. Since multiple trolley types can be utilized in a single train, there is flexibility. An additional benefit of operating with load carrier tow tractors as opposed to forklifts is the unobstructed view offered by a tow tractor, increasing the safety of work areas. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. This is vital for safety-sensitive places including airports and manufacturing facilities. Towing solutions are a good alternative to traditional forklifts to handle many single items. They are safe and easy to maneuver. A key benefit of these units is that typically, the operator doesn't need a license. Tow tractor operators do not need licenses since they don't lift loads off of the ground. There are three subtypes of load carrier tow tractors: 1. Pedestrian; 2. Stand-in; and 3. Rider-seated. Pedestrian Tow Tractors A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. It is compact, maneuverable and easy to use. Stand-in Tow Tractors Stand-in tow tractors are the most popular design for industries that involve order picking and horizontal transport in manufacturing. Stand-in tow tractors feature a tinier footprint compared to rider-seated editions and they offer a safe driver platform. Rider-Seated Tow Tractors Rider-seated tow tractors are similar to stand-in models except they offer a seated platform for the operator. These models are commonly used for transporting loads over farther distances such as moving checked baggage from the airport check-in to the aircraft at the terminal. These rider-seated options help to decrease driver fatigue allowing for greater efficiency. Heavy Duty Tow Tractors In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushing an aircraft back from the airport terminal without using the aircraft's own power is the pushback concept. This pushback process is done by using specially designed heavy duty tow tractors called pushback tractors or pushback tugs. Pushback tugs feature a low-profile

enabling them to travel under the aircraft's nose for easy attachment. Since the aircraft weight is heavy, these units need to be heavy in order to retain adequate ground friction to move the aircraft. Large aircraft tractors can weigh as much as fifty-four tons. These models have a driver's cab that has the option of being raised or lowered during reverse for better visibility. The unit is called a pushback tow tractor or pushback tug but it is additionally used to move aircraft in situations where taxiing is not safe or practical including into and outside of aircraft maintenance. The two subtypes of pushback tow tractors include conventional tow tractors and towbarless tow tractors. Conventional Pushback Tow Tractors Conventional units rely on a tow bar to connect the tug to the aircraft's nose landing gear. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. The tow bar that attaches to the tug can pivot vertically and laterally. In this manner, the tow bar acts as a large lever to rotate the nose landing gear. There are a towbar and precise tow fitting that acts as an adapter between the standard-sized tow pin and on the landing gear of the aircraft. On heavy towbars for large aircrafts, the towbar rides on its own wheels when not connected to an aircraft. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor. Towbarless Pushback Tow Tractors Towbarless tractors do not use a towbar; they scoop up the nose landing gear and lift it off the ground, allowing the tug to maneuver the aircraft. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.